

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



INTERNATIONAL PATENT COOPERATION TREATY (PCT)

(43) International Publication Date
6 May 2005 (06.05.2005)

PCT

(10) International Publication Number
WO 2005/040718 A1

(51) International Patent Classification:
G01B 9/02, G01N 21/47, A61B 3/12, 5/00

(74) Agent: MOUNTENEY, Simon, James; Marks & Clerk,
90 Long Acre, London WC2E 9RA (GB).

(21) International Application Number:
PCT/GB2004/004351

(22) International Filing Date: 14 October 2004 (14.10.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0324062.9 14 October 2003 (14.10.2003) GB


(71) Applicant (for all designated States except US): UNIVER-
SITY OF KENT [GB/GB]; Canterbury, Kent (GB).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AB, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, GR, HU, ID, IL, IN, IS, JP, KR,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MY, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,

[Continued on next page]

(54) Title: SPECTRAL INTERFEROMETRY METHOD AND APPARATUS



(57) Abstract: A spectral interferometry apparatus and method is provided to supply unambiguous profiles (A - scans free of mirror terms) of the reflectivity versus optical path difference and make difference between the positive and negative optical path difference or provide output in a selected interval of optical path differences. The apparatus comprises object optics that transfer a beam from an optical source to a target object (55) to produce an object beam and reference optics that produce a reference beam. Displacing means (57) are provided to produce a gap (g) between the object beam (41') and the reference beam (42'). Optical spectrum dispersing means (7) such as a grating or a prism receive the two relatively displaced beams, and disperse their spectral content onto a reading element such as a CCD. The combination of the displacing means and the optical spectrum dispersing means creates an intrinsic optical delay between the wavetrains of the object beam and the reference beam which can be used with the optical path difference in the interferometer to generate a channelled spectrum for the optical path difference in the interferometer on the reading element.

WO 2005/040718 A1

BEST AVAILABLE COPY

WO 2005/040718 A1

SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments